

COMPEX™ AEROPLY 600
Peel Ply

Ideally suited to aerospace applications.

FEATURES & BENEFITS

- Porous, polyester peel ply.
- Heat set and scoured, for use directly against laminates or bond lines.
- Available coated and non-coated, depending on user requirement.
- Approved on a range of OEM specifications for composite manufacture and metal bonding.
- This product is particularly recommended for use with phenolic resin systems.
- Also recommended for composite manufacture and metal bonding applications.

PRODUCT VARIANTS

- NAT – Scoured and heat set finish
- IO – International Orange for easy identification
- VLP – Very Low Porosity finish
- SRB – Super Release Blue (inert, heat stabilised, cross-linked polymer finish)

PROPERTIES

Maximum use temperature	204°C / 400°F
Color	Natural, blue and orange
Fabric type	Polyester
Fabric weight	85g/m ² / 2.5oz/yd ²

AVAILABILITY

Standard width	1.52m	60in
Standard length	274m	300yd
	Slit widths available to order	

STORAGE

No special storage conditions required.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr