

COMPEX™ AEROSPRAY2
Spray Adhesive

Ideally suited to bonding applications.

FEATURES & BENEFITS

- A repositionable, high strength adhesive spray compatible with gelcoat, barrier-coat, glass fiber matting and fiberglass laminates.
- Fully compatible with polyester and vinylester resins.
- Does not compromise the mechanical performance of laminates, even used in higher quantities than actually required.
- Does not compromise or inhibit the correct polymerization of resins.
- Does not weaken the degree of interlaminar adhesion between the different layers of a laminate.
- Contains a blue colorant which makes it possible to assess and regulate the quantity of AEROSPRAY2 applied, with the color disappearing during polymerization.

INSTRUCTIONS FOR USE

- Shake the aerosol well before use and ensure that the surfaces to be bonded are clean and dry
- Hold the aerosol vertically and spray an even layer of adhesive from a distance of 25cm (10in). It must not have the appearance of being wet. If this is the case, spray from a little further away
- To achieve optimum adhesion, spray the adhesive onto both surfaces to be joined and wait around one minute so that the solvent present in the adhesive may evaporate
- Finally, press the two surfaces firmly together to ensure good adhesion takes place
- After each use, purge the aerosol by holding it upside down.

AVAILABILITY

Contents: 500ml/1pint, but also available in larger quantities upon request.

STORAGE

- If the product is stored in the dark in its original, perfectly sealed container at a maximum temperature of 20°C (68°F), it will remain stable for at least 12 months from the date of production. If stored outside these conditions, the shelf life cannot be guaranteed. Storage for longer periods, or in conditions other than those specified, can alter the characteristics of the product, in some cases making it unusable
- AEROSPRAY2 is supplied in a pressurized container. Protect from direct sunlight and do not expose to temperatures of more than 50°C (122°F)

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr