

Ideally suited to infusion applications.

FEATURES & BENEFITS

- Flow medium for use with polyester and epoxy resins.
- Two variants available: CW3 at 50mm (2in) wide and CW3.50 – 100mm (4in) wide.
- 4mm thick feeder with high flow capacity for infusion and VARTM processes.
- Gives even resin flow over entire feeder surface, increasing productivity.
- Both variants are easy to fit into your production flow and install, with no sharp edges.
- Excellent chemical compatibility with polyester and epoxy resins.
- Consistent performance, meaning reproducible high quality finished products.

PROPERTIES

Maximum use temperature	254°C / 489°F
Color	Grey
Fiber	3D spacer matting of monofilaments in non-woven sleeve
Free flowing space	>75%
Weight	25g/m ² / 8oz/yd ²

AVAILABILITY

Width	FM2: 50mm / FM4: 100mm	FM2: 2in / FM4: 4in
Length	100m	109yd
Thickness	4mm	0.16in
Roll Weight	FM2: 3.5kg / FM4: 7kg	FM2: 8lbs / FM4: 16lbs

STORAGE

No special storage instructions.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr

