

COMPEX™ PFTAPE
Adhesive Tape

Ideally suited to tool maintenance applications.

FEATURES & BENEFITS

- High modulus PTFE tape
- Excellent release and temperature resistance
- Application is very simple, due to the tape having no backing liner, and it strips easily after use
- Ideal for many applications including temporary tool surface repairs, sealing of split moulds to prevent resin preparation, and where localised tool release in tight angles is required

PROPERTIES

| | | |
|--------------------------|----------------------|---------------|
| Maximum cure temperature | 180°C - 232°C | 356°F - 450°F |
| Color | Brown | |
| Adhesive | Silicone and Acrylic | |
| Carrier | PTFE | |
| Total thickness | 89µm | 0.0035in |
| Adhesive thickness | 38µm | 0.0015in |
| Tape thickness | 51µm | 0.002in |
| Elongation at break | 150% | |

AVAILABILITY

| | | |
|-----------------|-------------|-------------|
| Standard Width | Up to 100mm | Up to 3.9in |
| Standard Length | 33m | 36yd |

STORAGE

No special storage conditions required.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr