

COMPEX™ PP200
Peel Ply

Ideally suited to a wide range of composite processing applications.

FEATURES & BENEFITS

- Lightweight, porous nylon peel ply.
- Heat set and scoured, for use directly against laminates or bond lines, particularly where secondary bonding, painting or finishing is required.
- Imparts a fine weave pattern upon removal from the laminate.
- Strips cleanly and quickly from most commercial resin systems.
- Available coated and non-coated depending on user requirement.
- Recommended for composite manufacture and metal bonding applications.
- Shadowline does not recommend the use of woven nylon fabrics with phenolic resin or prepreg systems as acid in the catalyst can break down nylon materials. Therefore, we recommend that customers conduct their own internal compatibility tests.

PROPERTIES

Maximum use temperature	204°C / 400°F
Color	White
Fabric type	Nylon
Fabric weight	58g/m ² / 1.70oz/yd ²

AVAILABILITY

Standard width	1.47m	58in
Standard length	100m	109yd
	Slit widths available to order	

STORAGE

No special storage conditions required.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr