

COMPEX™ R620
Release Film

Ideally suited to aerospace applications.

FEATURES & BENEFITS

- High temperature, tough fluoropolymer release film with excellent release characteristics combined with high elongation.
- Suitable for use with all commonly used resin systems.
- Most commonly used in aerospace applications and has numerous OEM approvals.
- Clear blue or red for ease of identification on the cured laminate.
- Available perforated or non-perforated.

PROPERTIES

Maximum use temperature	232°C / 450°F
Color	Blue and red
Film	ETFE
Standard perforation patterns	Contact us for full details
Tensile strength (at break)	41.37MPa / 6000psi
Elongation (at break)	350%
Yield	10.2m ² /kg / 110 ft ² /lb/mil

AVAILABILITY

Thicknesses	12, 15, 20 and 25µm	0.0005, 0.0006, 0.001 and 0.002in
Standard length	Available on request	

STORAGE

Store in original packaging.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr