

COMPEX™ R888
Release Film

Ideally suited to medium temperature applications.

FEATURES & BENEFITS

- Silicone coated nylon fabric.
- Coated with heat cured silicone release solution, to aid removal from the cured laminate.
- Some phenolic resins are known to adhere to nylon release fabrics, and it is therefore recommended that the customer conduct their own internal compatibility tests.
- When using release fabrics on composite laminates that will be subject to secondary bonding or painting operations, there is a potential for minor transfer onto the component, despite the release solution being fully polymerised. It is therefore recommended that prior to bonding or painting the laminate should be suitable prepared (industry standard method is preparation by slight abrading or sanding of the surface followed by cleaning with an approved solvent).

PROPERTIES

Maximum use temperature	204°C / 400°F
Color	White with red pinstripes (Green is also available on request)
Fabric type	Nylon
Fabric weight	75g/m ² / 2.2oz/yd ²
Release coating	Silicone

AVAILABILITY

Standard width	1.52m	60in
Standard length	100m	109yd
	Slit widths available	

STORAGE

No special storage conditions required.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr