

COMPEX™ VV270-3
QRC Socket Connector**DESCRIPTION**

This socket connector is for use in high temperature autoclaves and ovens, high temperature tooling and associated equipment. QRC Socket is female threaded connector. It is easily maintained by releasing without the need to be removed from the hose.

Socket has a threaded female fitting, designed in the way to receive vacuum hose VV270-1.

All coupling parts are manufactured from stainless steel and manufactured to ISO B.

This product is used in various manufacturing processes of parts made of composite.

**TECHNICAL DATA**

Material type	Carbon Steel
Material type of O-ring seals	High Temperature Viton 270°C
Coupling size	1/4
Threaded size	1/4 inch female BSP
Maximum use temperature	270°C
Maximum autoclave pressure	10 Bar

Storage conditions: It is recommended to store at temperature from +10°C until +30°C in the original packing.

NOTE

All end fittings are 100% vacuum tested after assembly.
Socket can be delivered with any tread style (for example NPT) on special order.
Recommended maintenance interval 1000 hours based on operating temperatures up to 180°C when using our connections.

CONTACT US:

Shadowline Polimer / Atatürk Mahallesi Erzincan Sokak No:19 34758 Ataşehir, İstanbul/Türkiye
T: + 90 216 575 1162 | F: + 90 216 577 2549 | info@shadowline.com.tr